

GENERAL NOTES

1.1 FABRICATION SHALL BE IN ACCORDANCE WITH METAL BUILDING SUPPLIER. STANDARD PRACTICES 2.6 THE BUYER/END USE CUSTOMER IS RESPONSIBLE FOR OVERALL PROJECT COORDINATION. IN COMPLIANCE WITH THE APPLICABLE SECTIONS, RELATING TO DESIGN REQUIREMENTS AND ALLOWABLE STRESSES OF THE LATEST EDITION OF THE "AWS STRUCTURAL WELDING CODE D1.1 AND D1.3".

1.2	MATERIALS	ASTM DESIGNATION	MIN. YIELD STRENGTH
	HOT ROLLED STEEL SHAPES (W, & C)	A572	Fy = 50 KSI
	HOT ROLLED STEEL ANGLES (L)	A36	Fy = 36 KSI
	STEEL PIPES	A500	Fy = 42 KSI
	STRUCTURAL TUBING	A500	Fy = 42 KSI
	STRUCTURAL STEEL WEB PLATE		
	STRUCTURAL STEEL FLANGE PLATES/BARS	A529/A572	Fy = 55 KSI
	COLD FORMED LIGHT GAGE	A653/A1011	Fy = 55 KSI
	ROOF & WALL SHEETS	A792/A653	Fy = 50, 80 KSI EXTRA HIGH STRENGTH
	CABLE BRACE	A475 - TYPE 1	EXTRA HIGH STRENGTH
	ROD BRACE	A36	Fy = 36 KSI
			MIN. TENSILE STRENGTH
	MACHINE BOLTS & NUTS	A307	Fu = 60 KSI
	HIGH STRENGTH BOLTS (1" & LESS)	A325-TYPE 1	Fu = 120 KSI
	HIGH STRENGTH BOLTS (>1"ø TO 1 1/2"ø)	A325-TYPE 1	Fu = 105 KSI
	ANCHOR BOLTS (NOT SUPPLIED BY M.B.S.)	A36/A307/F1554	Fu = 60 KSI

PRIMER
SHOP PRIMER PAINT IS A RUST INHIBITIVE PRIMER WHICH MEETS THE END PERFORMANCE OF FEDERAL SPECIFICATION SSPC NO. 15 AND IS GRAY OXIDE IN COLOR. THIS PAINT IS NOT INTENDED FOR LONG TERM EXPOSURE TO THE ELEMENTS. METAL BUILDING SUPPLIER IS NOT RESPONSIBLE FOR ANY DETERIORATION OF THE SHOP PRIMER PAINT AS A RESULT OF IMPROPER HANDLING AND/OR JOBSITE STORAGE. METAL BUILDING SUPPLIER SHALL NOT BE RESPONSIBLE FOR ANY FIELD APPLIED PAINT AND/OR COATINGS.

(AISC CODE OF STANDARD PRACTICE, LATEST EDITION).

NOMINAL THICKNESS OF PRIMER WILL BE 1 MIL UNLESS OTHERWISE SPECIFIED IN CONTRACT DOCUMENTS.

1.4 GALVANIZED OR SPECIAL COATINGS:

.5 ALL BOLTS ARE 1/2" x 0'-1 1/4" A307 EXCEPT :

A) ENDWALL RAFTER SPLICE - 5/8" Ø x 0"-1 3/4" A325-N B) ENDWALL COLUMN TO RAFTER CONNECTION - (SEE WALL ELEVATION) C) MAIN FRAME CONNECTIONS - SEE CROSS SECTION D) FLANGE BRACE CONNECTIONS - 1/2" Ø x 0"-1 1/4" A325

NOTE: WASHERS ARE NOT SUPPLIED UNLESS NOTED OTHERWISE ON DRAWING

1.6 A325 BOLT TIGHTENING REQUIREMENTS

ALL HIGH STRENGTH BOLTS ARE A325—N UNLESS SPECIFICALLY NOTED OTHERWISE. HOLES ARE NOT SLOTTED AND DESIGN IS BEARING CONNECTION. STRUCTURAL BOLTS SHALL BE TIGHTENED BY THE "TURN-OF-THE-NUT" METHOD IN ACCORDANCE WITH THE LATEST EDITION AISC "SPECIFICATION FOR STRUCTURAL JOINTS" USING ASTM A325 OR A490 BOLTS, WHEN SPECIFICALLY REQUIRED. A325—N BOLTS ARE SUPPLIED WITHOUT WASHER UNLESS OTHERWISE NOTED ON THE DRAWINGS.

ALL BOLTED CONNECTIONS UNLESS NOTED ARE DESIGNED AS BEARING TYPE CONNECTIONS WITH BOLT THREADS NOT EXCLUDED FROM THE SHEAR PLANE.

BUILDINGS IN SEISMIC DESIGN CATEGORY C OR LOWER AND/OR WITH CRANE SYSTEMS 10 TONS OR LESS DO NOT REQUIRE TURN OF THE NUT PRE TENSIONING

.7 CLOSURE STRIPS ARE FURNISHED (IF ORDERED) FOR APPLICATION:

INSIDE- UNDER ROOF PANELS & BASE OF WALL PANELS

OUTSIDE - BETWEEN ROOF PANELS & RIDGE CAF BETWEEN WALL PANELS & EAVE/GABLE TRIM

.8 <u>ERECTION NOTE:</u>
ALL BRACING. STRAPPING. & BRIDGING SHOWN AND PROVIDED BY M.B.S. FOR THIS BUILDING IS ALL BRACING, STRAPPING, & BRIDGING SHOWN AND PROVIDED BY M.B.S. FOR THIS BUILDING REQUIRED AND SHALL BE INSTALLED BY THE ERECTOR AS A PERMANENT PART OF THE STRUCTURE. IF ADDITIONAL BRACING IS REQUIRED FOR STABILITY DURING ERECTION, IT SHALL BE THE ERECTOR'S RESPONSIBILITY TO DETERMINE THE AMOUNT OF SUCH BRACING AND TO PROCURE AND INSTALL AS NEEDED.

1.9 ERECTION AND UNLOADING NOT BY G.W.B.

1.10 SHORTAGES

ANY CLAIMS OR SHORTAGES BY BUYER MUST BE MADE TO M.B.S. WITHIN FIVE (5) WORKING DAYS AFTER DELIVERY, OR SUCH CLAIMS WILL BE CONSIDERED TO HAVE BEEN WAIVED BY THE

CORRECTIONS OF ERRORS AND REPAIRS (MBMA 6.10)
CLAIMS FOR CORRECTION OF ALLEGED MISFITS WILL BE DISALLOWED UNLESS M.B.S. SHALL
HAVE RECEIVED PRIOR NOTICE THEREOF AND ALLOWED REASONABLE INSPECTION OF SUCH
MISFITS. THE CORRECTION OF MINOR MISFITS BY THE USE OF DRIFT PINS TO DRAW THE COMPONENTS INTO LINE, MODERATE AMOUNTS OF REAMING, CHIPPING AND CUTTING, AND THE REPLACEMENT OF MINOR SHORTAGES OF MATERIAL ARE A NORMAL PART OF ERECTION AND ARE NOT SUBJECT TO CLAIM. NO PART OF THE BUILDING MAY BE RETURNED FOR ALLEGED MISFITS WITHOUT THE PRIOR APPROVAL OF M.B.S.

BUYER/END USE CUSTOMER RESPONSIBILITIES

IT IS THE RESPONSIBILITY OF THE BUYER/END USE CUSTOMER TO OBTAIN APPROPRIATE APPROVALS AND SECURE NECESSARY PERMITS FROM CITY, COUNTY, STATE, OR FEDERAL AGENCIES AS REQUIRED, AND TO ADVISE/RELEASE M.B.S. TO FABRICATE UPON RECEIVING

METAL BUILDING SUPPLIER (HEREAFTER REFERRED TO AS M.B.S.)
STANDARD SPECIFICATIONS APPLY UNLESS STIPULATED OTHERWISE IN THE CONTRACT
DOCUMENTS M.B.S. DESIGN, FABRICATION, QUALITY CRITERIA, STANDARDS, PRACTICE,
METHODS AND TOLERANCES SHALL GOVERN THE WORK WITH ANY OTHER INTERPRETATIONS TO THE CONTRARY NOTWITHSTANDING, IT IS UNDERSTOOD BY BOTH PARTIES THAT THE BUYER/END USE CUSTOMER IS RESPONSIBLE FOR CLARIFICATION OF INCLUSIONS OR

EXCLUSIONS FROM THE ARCHITECTURAL PLANS AND/OR SPECIFICATIONS.

IN CASE OF DISCREPANCIES BETWEEN M.B.S. STRUCTURAL STEEL PLANS AND PLANS FOR OTHER TRADES, M.B.S. PLANS SHALL GOVERN. (SECTION 3 AISC CODE OF STANDARD PRACTICES, LATEST EDITION)

APPROVAL OF M.B.S. DRAWINGS AND CALCULATIONS INDICATE THE M.B.S. HAS CORRECTLY INTERPRETED AND APPLIED THE CONTRACT DOCUMENTS. THIS APPROVAL CONSTITUTES THE CONTRACTOR/OWNERS ACCEPTANCE OF THE M.B.S. DESIGN CONCEPTS, ASSUMPTIONS, AND LOADING. (SECTION 4 AISC CODE AND MBMA 3.3.3)

ONCE THE BUYER/END USE CUSTOMER HAS SIGNED M.B.S. APPROVAL PACKAGE AND THE ONCE THE BUTTERY BIT OF COSTOMER AND SHORES SHALL BE BILLED TO THE BUTER!

END USE CUSTOMER INCLUDING MATERIAL ENGINEERING AND OTHER COSTS. AN ADDITIONAL
FEE MAY BE CHARGED IF THE PROJECT MUST BE MOVED FROM THE FABRICATION AND
SHIPPING SCHEDULE.

ALL INTERFACE, COMPATIBILITY, AND DESIGN CONSIDERATIONS
CONCERNING ANY MATERIALS NOT FURNISHED BY M.B.S. AND M.B.S. STEEL SYSTEM ARE TO BE
CONSIDERED AND COORDINATED BY THE BUYER/END USE CUSTOMER. SPECIFIC DESIGN CRITERIA
CONCERNING THIS INTERFACE BETWEEN MATERIALS MUST BE FURNISHED BEFORE RELEASE FOR FABRICATION OR M.B.S. ASSUMPTIONS WILL GOVERN (AISC CODE OF STANDARD PRACTICE,

2.7 IT IS THE RESPONSIBILITY OF THE BUYER/FND USE CUSTOMER TO INSURE THAT M.B.S. PLANS IT IS THE RESPONSIBILITY OF THE BUYER/END USE CUSTOMER TO INSURE THAT M.B.S. PLANS COMPLY WITH THE APPLICABLE REQUIREMENTS OF ANY GOVERNING BUILDING AUTHORITIES. THE SUPPLYING OF SEALED ENGINEERING DATA AND DRAWINGS FOR THE METAL BUILDING SYSTEM DOES NOT IMPLY OR CONSTITUTE AN AGREEMENT THAT M.B.S. OR ITS DESIGN ENGINEERS ARE ACTING AS THE ENGINEER OF RECORD OR DESIGN PROFESSIONAL FOR A CONSTRUCTION PROJECT. THESE DRAWINGS ARE SEALED ONLY TO CERTIFY THE DESIGN OF THE STRUCTURAL COMPONENTS FURNISHED BY M.B.S.

2.8 THE BUYER/END USE CUSTOMER IS RESPONSIBLE FOR SETTING OF ANCHOR BOLTS AND THE BUYER/END USE CUSTOMER IS RESPONSIBLE FOR SETTING OF ANCHOR BOLIS AND ERECTION OF STEEL IN ACCORDANCE WITH M.B.S. "FOR ERECTION" DRAWINGS ONLY. TEMPORARY SUPPORTS SUCH AS GUYS, BRACES, FALSE WORK, CRIBBING OR OTHER ELEMENTS REQUIRED FO THE ERECTION OPERATION SHALL BE DETERMINED, FURNISHED AND INSTALLED BY THE ERECTOR NO ITEMS SHOULD BE PURCHASED FROM A PRELIMINARY SET OF DRAWINGS, INCLING ANCHOR BOLTS. USE ONLY FINAL "FOR ERECTION" DRAWINGS FOR THIS USE. (AISC CODE OF STANDARD PRACTICE, LATEST EDITION.)

2.9 METAL BUILDING SUPPLIER IS RESPONSIBLE FOR THE DESIGN OF THE ANCHOR BOLTS TO PERMIT THE TRANSFER OF FORCES BETWEEN THE BASE PLATE AND THE ANCHOR BOLT IN SHEAR, BEARING AND TENSION, BUT IT IS NOT RESPONSIBLE FOR THE TRANSFER OF ANCHOR BOLT FORCES TO THE CONCRETE OR THE ADEQUACY OF THE ANCHOR BOLT IN RELATION TO THE CONCRETE.

UNLESS OTHERWISE NOTED PROVIDED IN THE ORDER DOCUMENTS, M.B.S. DOES NOT DESIGN AND UNLESS OTHERWISE NOTED PROVIDED IN THE ORDER DOCUMENTS, M.B.S. DOES NOT DESIGN AND IS NOT RESPONSIBLE FOR THE DESIGN, MATERIAL AND CONSTRUCTION OF THE FOUNDATION OR FOUNDATION OR POUNDATION OR PROVIDED THE FOUNDATION OR STATE OF THE BUILDING, OTHER IMPOSED LOADS, AND BEARING CAPACITY OF THE SOIL AND OTHER CONDITIONS OF THE BUILDING SITE. IT IS RECOMMENDED THAT THE ANCHORAGE AND FOUNDATION OF THE BUILDING BUSINGS BY A REGISTERED PROFESSIONAL ENGINEER EXPERIENCED IN THE DESIGNE DRY A REGISTERED PROFESSIONAL ENGINEER EXPERIENCED IN THE DESIGN OF SUCH STRUCTURES. (LATEST MBMA LOW RISE BUILDING SYSTEMS MANUAL)

2.10 NORMAL ERECTION OPERATIONS INCLUDE THE CORRECTIONS OF MINOR MISFITS BY MODERATE ONDRIVAL ERECTION OPERATIONS INCLODE THE CORRECTIONS OF MINOR MISTIS BY MODERATE AMOUNTS OF REAMING, CHIPPING, WELDING OR CUTTING, AND THE DRAWING OF ELEMENTS INTO LINE THROUGH THE USE OF DRIFT PINS. ERRORS WHICH CANNOT BE CORRECTED BY THE FOREGOING MEANS OR WHICH REQUIRE MAJOR CHANCES IN MEMBER CONFIGURATION ARE TO BE REPORTED IMMEDIATELY TO M.B.S. BY THE BUYER/END USE CUSTOMER, TO ENABLE WHOEVER IS RESPONSIBLE EITHER TO CORRECT THE ERROR OR TO APPROVE THE MOST EFFICIENT AND ECONOMIC METHOD OF CORRECTION TO BE USED BY OTHERS. (AISC CODE OF STANDARD PROVIDED LATEST ENTITION) PRACTICE LATEST EDITION)

2.11 NEITHER THE FABRICATOR NOR THE BUYER/END USE CUSTOMER WILL CUT, DRILL OR OTHERWISE ALTER HIS WORK, OR THE WORK OF OTHER TRADES, TO ACCOMMODATE OTHER TRADES, UNLESS SUCH WORK IS CLEARLY SPECIFIED IN THE CONTRACT DOCUMENTS. WHENEVER SUCH WORK IS SOUCH WORK IS CLEARLY SPECIFIED IN THE CONTRACT DOCUMENTS. WHENEVER SOUCH WORK SPECIFICD, THE BUYER/END USE CUISTOMER IS RESPONSIBLE FOR FURNISHING COMPLETE INFORMATION AS TO MATERIALS, SIZE, LOCATION AND NUMBER OF ALTERATIONS PRIOR TO PREPARATION OF SHOP DRAWINGS. (AISC CODE OF STANDARD PRACTICE LATEST EDITION)

2.12 <u>WARNING</u> IN NO CASE SHOULD GALVALUME STEEL PANELS BE USED IN CONJUNCTION WITH LEAD OR COPPER BOTH LEAD AND COPPER HAVE HARMFUL CORROSIVE EFFECTS ON THE GALVALUME ALLOY COATING WHEN THEY ARE IN CONTACT WITH GALVALUME STEEL PANELS. EVEN RUN-OFF FROM COPPER FLASHING, WIRING, OR TUBING ONTO GALVALUME SHOULD BE

2.13 SAFETY COMMITMENT METAL BUILDING SUPPLIER HAS A COMMITMENT TO MANUFACTURE QUALITY BUILDING COMPONENTS THAT CAN BE SAFELY ERECTED. HOWEVER, THE SAFETY COMMITMENT AND JOB SITE PRACTICES OF THE ERECTOR ARE BEYOND THE CONTROL OF M.B.S. IT IS STRONGLY RECOMMENDED THAT SAFE WORKING CONDITIONS AND ACCIDENT PREVENTION PRACTICES BE THE TOP PRIORITY OF ANY JOB SITE. LOCAL, STATE, AND FEDERAL SAFETY AND HEALTH STANDARDS SHOULD ALWAYS BE FOLLOWED TO HELP INSURE WORKERS SAFETY MAKE CERTAIN ALL EMPLOYEES KNOW THE SAFEST AND MOST PRODUCTIVE WAY OF ERECTING A BUILDING. EMERGENCY PROCEDURES SHOULD BE KNOWN TO ALL EMPLOYEES. DAILY MEETINGS HIGHLIGHTING SAFETY PROCEDURES ARE ALSO RECOMMENDED. THE USE OF HARD HATS, RUBBER SOLE SHOES FOR ROOF WORK, PROPER EQUIPMENT FOR HANDLING MATERIAL, AND SAFETY NETS WHERE APPLICABLE, ARE RECOMMENDED.

2.14 ROOF DRAINAGE SYSTEMS (GUTTER, DOWNSPOUTS, ETC.) MUST BE FREE OF ANY OBSTRUCTION TO ENSURE SMOOTH OPERATION AT ANY GIVEN TIME.


2.15 IT IS RECOMMENDED BY FACTORY MUTUAL (REFERENCE B2.44) THAT ROOFS BE CLEARED OF SNOW WHEN HALF OF THE MAXIMUM SNOW DEPTH IS REACHED. THE MAXIMUM SNOW DEPTH CAN BE ESTIMATED BASED ON THE DESIGN SNOW LOAD AND THE DENSITY OF SNOW AND/OR ICE BUILDUP. SEE TABLE BELOW.


EQUIVALENT SNOW HEIGHT AT ROOF (IN INCHES)	RECOMMENDED SNOW HEIGHT WHEN SNOW REMOVAL SHOULD START (IN INCHES)				
16.60	8.30				
17.25	8.62				
17.90	8.95				
18.55	9.28				
19.20	9.60				
19.85	9.92				
20.50	10.25				
21.15	10.58				
21.80	10.90				
22.45	11.22				
23.10	11.55				
23.75	11.88				
24.40	12.20				
	(IN INCHES) 16.60 17.25 17.90 18.55 19.20 19.85 20.50 21.15 21.80 22.45 23.10 23.75				

FOR SNOW/ICE REMOVAL PROCEDURE, REFER TO METAL BUILDING SYSTEM MANUAL 2002 FDITION, SECTION A8 4, PAGE XI-A8-2

		BUILDING LOADS	
	THIS STRUCTURE HAS BEEN DESIGNED	IN ACCORDANCE WITH THE FOLLOWING AS INDICATED:	OHK. OHK.
BE RIA R	DESIGN LOADS: DESIGN CODE / WIND CODE OCCUPANCY / RISK CATEGORY ENCLOSURE ROOF DEAD LOAD (D) (PSF) ROOF COLLATERAL LOAD (C) (PSF) WIND LOAD ULTIMATE WIND SPEED, (VULT) (MPH)	: IBC-21 : II-Normal : Enclosed : 3.45 : 22.00	ISSUE DATE DWN. APPROVAL W/08/24 MEZ PERMIT 07/08/24 SB ERECTION 08/35/24 PKD ISED ERECTION 01/08/25 PKD ERECTION 01/08/25 P
RY FOR OR. OR	WIND EXPOSURE CATEGORY INTERNAL PRESSURE COEFFICIENT, (GCpi) WALL PANEL DESIGN WIND PRESSURE (PSF) WIND ENCLOSURE CLASSIFICATION	: 0.18/-0.18 : 28.53/-30.94 : Enclosed	APPP PEE FEE
MIT MIT ND OR	LIVE LOAD PRIMARY FRAMING (PSF) TRIB. AREA REDUCTION SECONDARY FRAMING (PSF) SNOW LOAD GROUND SNOW LOAD, (Pg) (PSF)	: 20.00 : No : 20.00	THOUSE OF STEEN BUILDINGS.COM
JMN AND	ROOF SNOW LOAD, (Pf) (PSF) SNOW EXPOSURE FACTOR, (Ce) SNOW IMPORTANCE FACTOR, (Is) THERMAL FACTOR, (Ct) SEISMIC LOAD SEISMIC LOAD SEISMIC LASSIFICATION	: 80.00 : 1.00 : 1.00 : 1.20	SRAND JUNCTION, PHONE: (800)-49, W.GREATWESTERNBL
BE	SITE CLASSIFICATION SPECTRAL RESPONSE ACCELERATION SPECTRAL RESPONSE COEFFICIENTS SEISMIC DESIGN CATEGORY	:D :Ss = 0.303 :S1 = 0.083 :Sds = 0.315 :Sd1 = 0.133 :B	GRAND PHONE WWW.GREA
VISE ESS S	BASIC SEISMIC FORCE RESISTING SYSTEM TOTAL DESIGN BASE SHEAR, (V) (KIPS)	:STEEL SYSTEM NOT SPECIFICALLY DETAILED FOR RESISTANCE :RIGID FRAMES (OMF) :BRACED FRAMES (OCBF/OMF) :LONGITUDINAL = 18.31 :TRANSVERSE = 18.34	21 0 COVE
.S.	RESPONSE MODIFICATION FACTORS, (R) SEISMIC RESPONSE COEFFICIENTS, (Cs)	:RIGID FRAMES = 3.00 Ω = 3.00 :SW WIND BENT = 3.00 Ω = 3.00 :RIGID FRAMES = 0.1050	2 OF
ND E BER	ANALYSIS PROCEDURE USED OTHER LOADS/REQUIREMENTS	:SW WND BENT = 0.1050 :EQUIVALENT LATERAL FORCE PROCEDURE	
ETS N	OTHER LOADS/ REQUIREMENTS		CUSTOMER NAME: PROJECT NAME: PROJECT COCATION: PROJECT COUNTY: PROJECT COUNTY: CUSTOMER EMAIL: SCALE: N.T.S. SHEET NUMBER: SHEET TILE: SHEET TILE:
2	BUILDING DESCRIPTION: WIDTH (FT) : 40.00 LENGTH (FT) : 84.00 EAVE HEIGHT AT BSW (FT): 12.00 EAVE HEIGHT AT FSW (FT): 12.00 ROOF SLOPE AT BSW : 4.0:12 ROOF SLOPE AT FSW : 4.0:12 BAY SPACING (FT) : 1 AT 24, 3 AT 20 COVERING AND TRIMS:		
	ROOF PANELS & TRIMS PANEL TYPE : 26 GA. PBR PANEL COLOR : REGAL RED (KYNAR TRIM COLORS GABLE/EAVE : SOLAR WHITE EAVE GUTTER : N/A WALL PANELS & TRIMS PANEL TYPE : 26 GA. PBR	ROOF SOFFIT PANELS & TRIMS PANEL TYPE : 26 GA. PBR PANEL COLOR : SOLAR WHITE TRIM COLORS : SOLAR WHITE	
	PANEL COLOR : ASH GRAY TRIM COLORS CORNER : SOLAR WHITE FRAMED OPENING : SOLAR WHITE DOWNSPOUTS : N/A BASE : ASH GRAY INSULATION ROOF INSULATION : N/A WALL INSULATION : N/A		THIS SEAL PERTAINS ONLY TO THE MATERIALS DESIGNED AND SUPPLIED BY GREAT WESTERN BUILDINGS. THE DRAWINGS AND THE METAL BUILDINGS WHICH THEY RESTERN BUILDINGS. THE REGISTERED PROFESSIONAL ENGINEER WHOSE SEAL AND SIGNATURE APPEARS ON THESE DRAWINGS IS EMPLOYED BY GREAT WESTERN BUILDINGS AND DOES NOT SERVE AS OR REPRESENT THE OVERALL PROJECT ENGINEER OF RECORD AND SHALL NOT BE CONSTRUED AS SUCH.

BUILDING LOADS






THIS SEAL PERTAINS ONLY TO THE MATERIALS DESIGNED AND SUPPLIED BY GREAT WESTERN BUILDINGS. THE DRAWINGS AND THE METAL BUILDING WHICH THEY REPRESENT ARE THE PRODUCT OF GREAT WESTERN BUILDINGS. THE REGISTERED PROFESSIONAL ENGINEER WHOSE SEAL AND SIGNATURE APPEARS ON THESE DRAWINGS IS EMPLOYED BY GREAT WESTERN BUILDINGS AND DOES NOT SERVE AS OR REPRESENT THE OVERALL PROJECT ENGINEER OF RECORD AND SHALL NOT BE CONSTRUED AS


BOL


ANCHOR


DESIGN OF SHEAR ANGLES, TENSION PLATES, HAIRPINS, AND ANY OTHER EMBEDDED MATERIAL IN THE CONCRETE SHALL BE DESIGNED


AND PROVIDED BY OTHERS.











RIGIE	FRAME:		MAXIMUM	REACTION	IS, ANCH	HOR BOLT	S, & BASI	E PLATE	ES				
Fri Lir		Load Id	Hmax H	umn_Reac V Vmax	tions(k Load Id	Hmin H	V Vmin	Bol QTY	t(in) DIA	Base Width	e_Plate(in) Length	Thick	Grout (in)
5	D	6 1	1.1 0.7	6.3 8.4	9 7	-0.9 -0.7	-0.9 -1.5	4	0.750	6.000	12.00	0.375	0.0
5	А	10 1	0.9 -0.7	-0.9 8.4	5 8	-1.1 0.7	6.3 -1.5	4	0.750	6.000	12.00	0.375	0.0
5	С	5 11	1.5 0.0	-1.9 17.9	3 8	-1.3 0.0	−1.8 −1.1	4	0.750	6.000	8.000	0.375	0.0
5	В	4 12	1.5 0.0	-1.9 17.9	2 7	-1.3 0.0	−1.8 −1.1	4	0.750	6.000	8.000	0.375	0.0

RIGID	FRAME:		MAXIMUM	REACTION	S, ANC	HOR BOL	S, & BAS	E PLATI	ES				
Frm Line	Col Line	Load Id	Hmax H	umn_Reac V Vmax	tions(k Load Id	Hmin H	V	Bol QTY	t(in) DIA	Base Width	e_Plate(in) Length	Thick	Grout (in)
3*	D	1	21.8	47.1	7	-2.5	-4.3	4	0.750	8.000	20.00	0.375	0.0
3*	А	8 1	2.5 -21.8	-4.3 47.1	1 8	-21.8 2.5	47.1 -4.3	4	0.750	8.000	20.00	0.375	0.0
3*	FRAME lir	nes:	3 4										

RIGID FRAI	ME: BAS	C COLUMN REACT	IONS (k)			
FRAME Column Line Line 2 D 2 A	Horz Vert	Horz Vert	Horz Vert	Horz Vert 17.6 38.7	Wind_Left1- Horz Vert -5.7 -10.7 0.5 -7.3	-Wind_Right1- Horz Vert -0.5 -7.3 5.7 -10.7
FRAME Column Line Line 2 D 2 A	Wind_Left2- Horz Vert -5.2 -6.9 0.1 -3.5	Horz Vert	Wind_Long1- Horz Vert -0.7 -8.0 1.8 -7.1	Horz Vert	Horz Vert	Seismic_Right Horz Vert 2.3 1.2 2.3 -1.2
FRAME Column Line Line 2 D 2 A	F1UNB_SL_L- Horz Vert 14.0 36.9 -14.0 20.4	F1UNB_SL_R- Horz Vert 14.0 20.4 -14.0 36.9				
FRAME Column Line Line 3* D 3* A	Dead Horz Vert 1.0 2.6 -1.0 2.6	Horz Vert	Horz Vert 4.0 8.8	Horz Vert 16.0 35.2	Wind_Left1- Horz Vert -5.2 -9.8 0.5 -6.6	-Wind_Right1- Horz Vert -0.5 -6.6 5.2 -9.8
FRAME Column Line Line 3* D 3* A	Wind_Left2- Horz Vert -4.7 -6.3 0.1 -3.1	-Wind_Right2- Horz Vert -0.1 -3.1 4.7 -6.3	Horz Vert -0.6 -7.3	Wind_Long2- Horz Vert -1.7 -6.5 0.6 -7.3	-Seismic_Left Horz Vert -2.1 -1.1 -2.1 1.1	Seismic_Right Horz Vert 2.1 1.1 2.1 -1.1
FRAME Column Line Line 3* D 3* A	F2UNB_SL_L- Horz Vert 12.7 33.6 -12.7 18.6	F2UNB_SL_R- Horz Vert 12.7 18.6 -12.7 33.6				
FRAME Column Line Line 5 D 5 A 5 C 5 B	Dead Horz Vert 0.0 0.5 0.0 0.5 0.0 0.9 0.0 0.9	Horz Vert	Horz Vert	Horz Vert	Wind_Left1- Horz Vert -1.2 -2.9 -1.2 -1.0 0.0 -1.7 0.0 -2.7	Horz Vert 1.2 −1.0
Line Line	Wind_Left2- Horz Vert -1.5 -2.0 -0.8 0.0 0.0 -0.9 0.0 -1.9	-Wind_Right2- Horz Vert 0.8 0.0 1.5 -2.0 0.0 -1.9 0.0 -0.9	Wind_Press- Horz Vert 0.0 0.0 0.0 0.0 -2.2a 0.0 -2.2a 0.0	Horz Vert 0.0 0.0 0.0 0.0	Wind_Long1- Horz Vert 0.8 -1.6 -0.3 -1.9 0.0 -2.7 0.0 -0.8	Wind_Long2- Horz Vert 0.3 -1.9 -0.8 -1.6 0.0 -0.8 0.0 -2.7
Line Line 5 D	-Seismic_Left Horz Vert -1.2 -1.4 -1.2 1.4 0.0 1.9	Seismic_Right Horz Vert 1.2 1.4 1.2 -1.4 0.0 -1.9	-Seismic_Long Horz Vert 0.0 0.0 0.0 0.0	F3UNB_SL_L- Horz Vert 0.3 6.2 -0.3 1.9 0.0 13.8	F3UNB_SL_R- Horz Vert 0.3 1.9 -0.3 6.2 0.0 4.6	

a - Out-Of-Plane Horizontal Load

NOTES FOR REACTIONS

2	FUR REACTIONS	
the	ding reactions are based on following building data: Width (ft) Length (ft) Eave Height (ft) Roof Slope (rise/12) Dead Load (psf) Collateral Load (psf) Live Load (psf) Live Load (psf) Ultimate Wind Speed (mph) Wind Code Exposure Closed/Open Importance Wind Importance Seismic Seismic Zone Seismic Coeff (Fa*Ss)	40.00 84.00 12.00/12.00 4.0:12/4.0:12 3.45 22.00 20.00 80.00 115.00 IBC-21 C Enclosed 1.00 1.00 B
ID.	Description	

	Seismic Coeff (Fa*Ss)	=	0.47
D	Description		
2	Dead+Collateral+Snow+Slide_Snow Dead+Collateral+0.75Live+0.45Wind_L		

 2
 Dead+Collateral+0.75Live+0.45Wind_Long1R

 3
 Dead+Collateral+0.75Live+0.45Wind_Long2L

 4
 Dead+Collateral+0.75Snow+0.45Wind_Left1+0.75Snow_Drift

 5
 Dead+Collateral+0.75Snow+0.45Wind_Left1+0.75Slide_Snow

 6
 Dead+Collateral+0.75Snow+0.45Wind_Right1

 7
 0.6Dead+0.6Wind_Left1

 8
 0.6Dead+0.6Wind_Eft2

 10
 0.6Dead+0.6Wind_Right1

 10
 0.6Dead+0.6Wind_Right2

 10
 Dead+Collateral+73UNB_SL_L

 12
 Dead+Collateral+F3UNB_SL_R

 13
 0.6Dead+0.6Wind_Fressure+0.6Wind_Long1L

 15
 Dead+Collateral+E1UNB_SL_L

 Dead+Collateral+E1UNB_SL_L

14 0.6Dead+0.6Wind_Pressure+0.6Wind_Long1L
15 Dead+Collateral+E1UNB_SL_L
16 0.6Dead+0.6Wind_Suction+0.6Wind_Long2L
17 0.6Dead+0.6Wind_Pressure+0.6Wind_Long2L
18 Dead+Collateral+E1UNB_SL_R
19 0.6Dead+0.6Wind_Right1+0.6Wind_Suction
20 Dead+Collateral+E2UNB_SL_L
21 Dead+Collateral+E2UNB_SL_R

BUILD		BRACI	±	Reacti	DNS ions(k) - —Sei		Panel_	_Shear /ft)	
Loc	Line	Line	Horz "	Vert		Vert			Note
L_EW F_SW R EW	1 A 5	B,A 2,3	1.6 1.5	1.9 1.5	2.9 4.6	3.3 4.7			(b)
B_SW	D	2,3	1.5	1.5	4.6	4.7			(p)
(b)Wind (h)Rigid	bent frame	in bay, b e at endw	ase abov vall	e finish	floor				
Reaction Reaction	ns for n value	seismic ı es shown	represent are unfa	shear ctored	force, Eh	1			

ANCHO	R BOLT	SUMMA	\RY
QTY	LOCATE	DIA (in)	TYPE
O 4 O 4 O 4 Ø 16 Ø 32	JAMB ENDWALL PC ENDWALL FRAME	5/8" 5/8" 5/8" 5/8" 3/4" 3/4"	A307 A307 A307 A307 A307

MAXIM	um re	EACTIO	NC	
Part Id	Orient		(k) Wind Horz	
1	Trans.	0.0	0.6	

THIS SEAL PERTAINS ONLY TO THE MATERIALS
DESIGNED AND SUPPLIED BY GREAT WESTERN
BUILDINGS. THE DRAWINGS AND THE METAL
BUILDING WHICH THEY REPRESENT ARE THE
PRODUCT OF GREAT WESTERN BUILDINGS.
THE REGISTERED PROFESSIONAL ENGINEER WHOSE
SEAL AND SIGNATURE APPEARS ON THESE
DRAWINGS IS EMPLOYED BY GREAT WESTERN
BUILDINGS AND DOES NOT SERVE AS OR
REPRESENT THE OVERALL PROJECT ENGINEER OF
RECORD AND SHALL NOT BE CONSTRUED AS
SUCH.

GRAND JUNCTION, CO 81501 PHONE: (800)-497-2135 WWW.GREATWESTERNBUILDINGS.COM

RE

BOL

ANCHOR

9486

9

 Ω

AVE

3RD

1101

END	WALL COLUMN:		IN:	BASIC	BASIC COLUMN REACTIONS (k)										
Frm Line 1 1 1	Col Line D C B A	Dead Vert 0.4 1.0 1.0 0.4	Collat Vert 1.5 4.2 4.2 1.5	Live Vert 1.8 3.6 3.6 1.8	V: 7. 14. 14.		Wind_Le Horz 0.0 0.0 -1.6 0.0	eft1 Vert -2.7 -4.4 -5.1 0.2	Wind_R Horz 0.0 0.0 0.0 1.6	ight1 Vert -2.3 -2.5 -2.4 -4.8	Wind_Le Horz 0.0 0.0 -1.6 0.0	eft2 Vert -1.8 -3.2 -3.9 1.2	Wind Hor 0.0 0.0 0.0 1.6	-1.4 -1.3	Wind Press Horz -0.8 -2.2 -2.2
Frm Line 1 1 1	Col Line D C B A	Wind Suct Horz 0.9 2.4 2.4 0.9	Wind_L Horz 0.0 0.0 0.0 0.0	ong1 Vert -2.4 -3.8 -1.3 -2.6	Wind_L Horz 0.0 0.0 -0.9 0.0	Long2 Vert -1.6 -2.3 -5.2 -1.0	Seis Horz 0.0 0.0 -2.9 0.0	_Left Vert 0.2 -0.3 -4.2 4.3	Seis_ Horz 0.0 0.0 0.0 2.9	_Right Vert -0.2 0.3 3.3 -3.3	Seis Long Horz 0.0 0.1 0.1 0.0	H C C C	1UNB_S orz .0 .0 .0	SL_L- Vert 7.2 16.8 5.8 1.9	
Frm Line 1 1 1	Col Line D C B A	E1UNB_S Horz 0.0 0.0 0.0 0.0	SL_R- Vert 1.9 5.8 16.8 7.1												


ENDWALL COLUMN:


MAXIMUM REACTIONS, ANCHOR BOLTS, & BASE PLATES


Frm Line	Col Line	Load Id	Hmax H	umn_Reac V Vmax	tions(k Load Id	Hmin H	V Vmin	Bol QTY	t(in) DIA	Base Width	e_Plate(in) Length	Thick	Grout (in)
1	D	13 1	0.6 0.0	-1.4 9.0	14 13	-0.5 0.6	-1.2 -1.4	2	0.625	3.500	8.000	0.250	0.0
1	С	13 15	1.4 0.0	-2.0 22.0	14 13	-1.3 1.4	−1.7 −2.0	4	0.750	6.000	8.000	0.375	0.0
1	В	16 18	1.4 0.0	-2.5 22.0	17 16	-1.3 1.4	-2.5 -2.5	4	0.750	6.000	8.000	0.375	0.0
1	Α	19 1	0.6 0.0	-2.6 9.0	14 19	-0.5 0.6	-1.4 -2.6	2	0.625	3.500	8.000	0.250	0.0


CUSTOMER NAME:	<	ISSNE	DATE	DATE DWN.	CHK.	ENG.
PROJECT NAME:		APPROVAL	04/08/24 MEZ	MEZ	MEZ	RTS
PROJECT LOCATION:		PERMIT	07/26/24	8S	CAF	RTS
PROJECT COUNTY:		ERECTION	08/13/24 PKD	PKD	PKD	RTS
PROJECT END USE:						
CUSTOMER PHONE NUMBER:						
CUSTOMER EMAIL:						
SCALE: N. T.S.						
	1101 3RD AVE					
	GRAND JUNCTION, CO 81501					
SHEET NUMBER:	PHONE: (800)-497-2135					
6 OF 21	MOO SOINIG III I I I I I I I I I I I I I I I I					
- NO SULMBER	WWW.GREALWESTERNBOILDINGS.COM					
94863						
SHEET TITE:						
JICH SAIM - CM MCISIA						


THIS SEAL PERTAINS ONLY TO THE MATERIALS
DESIGNED AND SUPPLIED BY GREAT WESTERN
BUILDINGS. THE DRAWINGS AND THE METAL
BUILDING WHICH THEY REPRESENT ARE THE
PRODUCT OF GREAT WESTERN BUILDINGS.
THE REGISTERED PROFESSIONAL ENGINEER WHOSE
SEAL AND SIGNATURE APPEARS ON THESE
DRAWINGS IS EMPLOYED BY GREAT WESTERN
BUILDINGS AND DOES NOT SERVE AS OR
REPRESENT THE OVERALL PROJECT ENGINEER OF
RECORD AND SHALL NOT BE CONSTRUED AS
SUCH.














SIDEWALL SHEETING & TRIM: FRAME LINE A
PANELS: 26 GA. PBR - ASH GRAY




COM	IEC HON	PLATES
FRAM	E LINE	A
	QUAN	MARK
1	58	CL-103
2	26	CL-100
3	10	4" ZEE - 9"
4	1	4" ZEE - 18'-0"

THIS SEAL PERTAINS ONLY TO THE MATERIALS DESIGNED AND SUPPLIED BY GREAT WESTERN BUILDINGS. THE DRAWINGS AND THE METAL BUILDING WHICH THEY REPRESENT ARE THE PRODUCT OF GREAT WESTERN BUILDINGS. THE REGISTERED PROFESSIONAL ENGINEER WHOSE SEAL AND SIGNATURE APPEARS ON THESE DRAWINGS IS EMPLOYED BY GREAT WESTERN BUILDINGS AND DOES NOT SERVE AS OR REPRESENT THE OVERALL PROJECT ENGINEER OF RECORD AND SHALL NOT BE CONSTRUED AS SUCH.







SIDEWALL SHEETING & TRIM: FRAME LINE D
PANELS: 26 GA. PBR - ASH GRAY



REPRESENT THE OVERALL PROJECT ENGINEER OF RECORD AND SHALL NOT BE CONSTRUED AS



ENDWALL FRAMING: FRAME LINE 1 NOTE: F.L.F.O. = FIELD LOCATED FRAME OPENING



ENDWALL SHEETING & TRIM: FRAME LINE 1
PANELS: 26 GA. PBR - ASH GRAY


1 TABLE					· ·	(0	(0	(,,		\top					$\neg \neg$	
ME_LINE_1					ENG.	RTS	RTS	RTS								
QUAN PART	LENGTH		DETAIL		SH.	MEZ	CAF	PKD								
4 FL-60 6 FL-15 2 FL-601	10'-2" 8'-3" E 8 1/8" L 5 5/8" 1'-4" R 5 5/8" 7'-4" 3'-8"		TD75 TD36		DWN.	MEZ		PKD		\dagger	Н					
2 FL-601 1 FL-600	E 8 1/8" I 5 5/8"		TD85 TD12				SB SB									
1 FL-17	1'-4"				DATE	04/08/24	07/26/24	08/13/24								
l 2 FL-48	R 5, 5/8 7,-4"		TD12 TD51													
1 FL-52	3'-8"		TD52		Щ	JVAL	⊨	NOIT								
BOLT TABLE FRAME LINE 1					ISSUE	APPROVAL	PERMIT	ERECTION								
LOCATION		TYPE DIA		ENGTH												
ER-1/ER-1 COLUMNS/RAFTER	8 2	A325 5/8 A325 5/8	3" 1 3" 1	3/4" 1/2"		_						'				
MEMBER TABL		7.020 07.0		1/2			/	//	///)(81501	PHONE: (800)-497-2135 www.grfatwestfrnbluidings.com		
FRAME LINE 1		1.5107	F1.1			/	/ /	/			<u> </u>	1.1	GRAND JUNCTION, CO 8150	-21 DIX		
QUAN MAR 1 EB-		LENGT	1H 3 /8"		+		\dashv	/		\leq	Ć.	AVE	Ö	497 BUII	! !	
1 EB-	7 W12X14	3,-5	3/8"						_	\geq	\supset	1101 3RD	NO () – FRN	: :	
1 EC- 1 EC-	2 W8X10	10,-3	7/8 15/16	,,			/	$\langle \setminus$	~ ^\	\geq	\supset	1 3	NC.) (80 - S	:	9
1 EC- 1 EC-	3 W8X10 4 8×25C16	14'-3 10'-3	15/16 7/8"	,	(\	\dashv		V	_	_	110	\exists			
2 ER- 2 DJ- 1 DH-	1 W10X12	21'-0	3/4"			/	\		1	>	\sqrt{c}		N N	10N	į	SHEETING
	1 8x25C16	3'-3	1/2"	_			\	//	1/1				GR.	± ×		
10 G- 2 G- 2 G- 7 G-	1 W10X12 1 8x25C16 1 8x25C16 1 8x25Z16 2 8X25Z16 3 8X25Z16	11'-7 6'-6	15/16° 11/16°	,				\		\leq				≷		8
2 G- 2 G-	3 8X25Z16 4 8X25Z16	6 11/	16"	,,												
1 G-	5 8X25Z16	3'-9	5/8"													Z
1 CB- 1 CB-	1 CB0500 2 CB0500	15′-6 18'-4	H 3/8" 3/8" 7/8" 15/16 15/16 7/8" 1/2" 15/16" 11/16" 13/16 5/8" 1/4"											7		\geq
	FIELD WORK TABL													HO	63	DWALL FRAMING
	FRAME LINE 1 OID DETAIL DIME	ENSION 1	DIMEN	SION 2	-									2	48	
	1 SD202 1'-	7 7/16"	10'-4	1/16"										_	0	
	2 SD202 4'	7/16" 8 9/16"	8'-6 6'-11	5/16" 7/16"					- MBED							\rangle
	4 SD202 4' - 5 SD202 3' -	10 13/16"	9'-7	1/2"	Ę		:NOIL	Ë	USE:	ij	S.			,,		
	4 SD202 4'- 5 SD202 3'- 6 SD202 1'-	3 5/16"	_		CUSTOMER NAME:	PROJECT NAME:	PROJECT LOCATION:	PROJECT COUNTY:	PROJECT END USE:	CUSTOMER EMAIL:	z Z			SHEET NUMBER	JMBER	TILE
	CONNEC	CTION PLATE	ES		CUSTO	PROJEC	PROJE	PROJEC	PROJEC	CUSTO	SCALE:			SHEET	JOB NUMBER	SHEET
	FRAME	LINE 1 UAN MARK			-											
	1	18 CL-1														
	2 3	12 CL-1 6 CL-1														
	4	10 CL-5)													
		LANGE BRA RAME LINE		BLE												
	_	7ID QUAN	MARI	<	1											
		1 2	FB30		1											
					1											

THIS SEAL PERTAINS ONLY TO THE MATERIALS DESIGNED AND SUPPLIED BY GREAT WESTERN BUILDINGS. THE DRAWINGS AND THE METAL BUILDING WHICH THEY REPRESENT ARE THE PRODUCT OF GREAT WESTERN BUILDINGS.


THE REGISTERED PROFESSIONAL ENGINEER WHOSE SEAL AND SIGNATURE APPEARS ON THESE

REPRESENT THE OVERALL PROJECT ENGINEER OF RECORD AND SHALL NOT BE CONSTRUED AS


DRAWINGS IS EMPLOYED BY GREAT WESTERN BUILDINGS AND DOES NOT SERVE AS OR



ENDWALL FRAMING: FRAME LINE 5 NOTE: F.L.F.O. = FIELD LOCATED FRAME OPENING



ENDWALL SHEETING & TRIM: FRAME LINE 5 PANELS: 26 GA. PBR - ASH GRAY




	CONNECTION PLATES FRAME LINE 5							
	QUAN	MARK						
1 2 3 4	4 10 40 18	CL-109E 4" ZEE - 11" CL-103 CL-100						


THIS SEAL PERTAINS ONLY TO THE MATERIALS DESIGNED AND SUPPLIED BY GREAT WESTERN BUILDINGS. THE DRAWINGS AND THE METAL BUILDING WHICH THEY REPRESENT ARE THE PRODUCT OF GREAT WESTERN BUILDINGS. THE REGISTERED PROFESSIONAL ENGINEER WHOSE SEAL AND SIGNATURE APPEARS ON THESE DRAWINGS IS EMPLOYED BY GREAT WESTERN BUILDINGS AND DOES NOT SERVE AS OR REPRESENT THE OVERALL PROJECT ENGINEER OF RECORD AND SHALL NOT BE CONSTRUED AS

94863

ENDWALL

 $\bigcup_{i \in I} (i)$





BOLT TABLE ROOF PLAN LOCATION LENGTH TYPE DIA QUAN A325 A325 A325 A325 A325 5/8" 5/8" 5/8" 5/8" 5/8" EB-2 EB-3 1 1/2" 1 1/2" 1 1/2" 1 1/2" 1 1/2" 4 4 4 DWN. MEZ SB PKD GRAND JUNCTION, CO 81501 PHONE: (800)-497-2135 WWW.GREATWESTERNBUILDINGS.COM AVE 3RD 1101 PLAN 94863 FRAMING 9 9 ROOF

DESIGNED AND SUPPLIED BY GREAT WESTERN BUILDINGS. THE DRAWINGS AND THE METAL BUILDING WHICH THEY REPRESENT ARE THE PRODUCT OF GREAT WESTERN BUILDINGS. THE REGISTERED PROFESSIONAL ENGINEER WHOSE SEAL AND SIGNATURE APPEARS ON THESE DRAWINGS IS EMPLOYED BY GREAT WESTERN BUILDINGS AND DOES NOT SERVE AS OR REPRESENT THE OVERALL PROJECT ENGINEER OF RECORD AND SHALL NOT BE CONSTRUED AS

